

Document Reference No.  
93-68-EEC1300



## DECLARATION OF CONFORMITY FOR CE MARKING

Cooper Bussmann, Inc.  
P. O. Box 14460  
St. Louis, MO 63178 U.S.A.

declare under our sole responsibility that the product(s) to which this Declaration relates is/are in conformity with the Standard(s) or Normative Documents detailed below and follow the provisions of the Directives stated.

These products shall be installed, maintained and used in applications for which they were made, in accordance with professional practices, relevant installation standards and manufacturer's instructions. These products may be used by unskilled persons only as a replacement part to substitute for identical devices.

Catalog Reference or Designation of Products:

EDCC

Standard(s) or Normative Documents:

Low Voltage Fuse-Links. See attached sheet.

EEC Directive(s) applicable: Low Voltage

Place of Issue: St. Louis, MO U.S.A.

Date of Issue: April 18, 2005

Authorized Signature: 

Name and Position: Daniel B. Giblin  
Mgr., Industry Standards & Certifications

## LOW-VOLTAGE FUSE-LINKS

The low-voltage fuse-links listed on the Declaration of Conformity meet the essential requirements of the safety objectives of the Low-Voltage Directive for the following reasons:

1. **Marking** - These fuse-links are marked with the following information:
  - Manufacturer's name or trademark: Edison
  - Manufacturer's catalog or part number: EDCC
  - Rated voltage: 600 AC --- DC
  - Rated current: 0 - 30 A
  - Breaking capacity: 200 kA AC --- kA DC
2. **Dimensions** - These fuse-links have unique dimensions which exclude their installation in fuseholders for other types of fuse-links.
3. **Rated Frequency** - 45 to 62 Hz.
4. **Non-fusing Characteristic** - Carry 1.0 I<sub>N</sub> (100% of rating).
5. **Fusing Characteristics** - The fuse-link shall meet the following appropriate opening time requirements:
  - Open at 1.35 I<sub>N</sub> (135% of rating) in 60 minutes or less.
  - Open at 2.0 I<sub>N</sub> (200% of rating) in 4 minutes or less.
6. **Availability** - These fuse-links are available through a major distribution network in the European Union.
7. **Prior Sale** - These fuse-links have been available in the world market for over 3 years.
8. **Quality** - These fuse-links were manufactured in an ISO 9000 registered facility.